



model 1922

Wall Mounted Bottle Filler w/Drip Tray Drain

FEATURES & BENEFITS

STAINLESS STEEL VALVE

The push-button activated valve offers the only all stainless steel valve body that is machined out of solid bar stock, is fully serviceable through the front of the push button assembly offering access to the water control cartridge and integral water supply strainer, and with front access to the water stream height adjustment for easy maintenance without having to remove the valve. Operating pressure range of 30 to 90 psi (2.1 to 6.2 bar).

CONSTRUCTION

Heavy-duty 14 gauge Type 304 Stainless Steel bottle filler and drain brackets with a satin finish that resists stains and corrosion, and have soft rounded corners. Unit features vandal-resistant bottom plates, and a serviceable/replaceable dispensing nozzle.

ADA COMPLIANCE

ADA-compliant bottle filler required for wheel chair use, and for the standing person.

IN-WALL DRAIN

Drip tray captures unused water and lets it drain to the facilities waste lines.

LAMINAR FLOW

Adjustable, splash-free, 1 gpm (3.78 L) laminar flow.

MOUNTING OPTIONS

Select from mounting plate models to complete installation. Unit can mount on various wall types.

FOUNTAIN PUSH BUTTON

All chrome plated brass push button resists vandalism by allowing it to spin without unscrewing.



SPECIFICATIONS

Model 1922 wall mounted ADA-compliant bottle filler and drain shall include 100% lead-free waterways, satin stainless steel construction, 1 gpm (3.78 L) laminar flow, push-button operated stainless steel valve with front accessible cartridge and flow adjustment, drip tray drain, and stainless steel back panels (order models 1920 and 6468 if panels are not required).

APPLICATIONS

This type of wall mounted bottle filler may be placed in settings such as schools and other locations in and around office buildings with existing fountain installations where the temperature remains above freezing. Haws manufactures drinking fountains, faucets and electric water coolers to be lead-free by all known definitions including NSF/ANSI/CAN 61-Section 9, NSF/ANSI/CAN 372, California Proposition 65, and the Federal Safe Drinking Water Act. Product is compliant to California Health and Safety Code 116875 (AB 1953-2006), and NSF/ANSI/CAN 61: Q ≤ 1.

OPTIONS

Mounting Plate: Model 6700R mounting plate is used with the 1920 series bottle fillers for single or dual fountain retrofit installations.

Mounting Plate: Model 6700 universal mounting plate for most wall mounted fountains. Priced Separately.

For more information, visit www.hawsc.com or call (888) 640-4297.

